

WQ100T4 Diesel Generator Set 100kW

Open Skid Model





STANDARD FEATURES:

- Isuzu Liquid Cooled Engine
- Stamford Generator with Automatic Voltage Regulator—CSA approved
- Heavy duty steel skid base with anti-vibration isolators
- Digital generator controller with user friendly color display and auto start/stop
- Electronic governing- excellent frequency and load pick-up
- Extended run DEF tank
- Safety shutdown protection
- Operator Manuals
- Serviced and 100% Load Tested

Simple T4F after treatment uses Selective Catalytic Reduction exhaust aftertreatment to meet emissions standards. No need for diesel particulate filter (DPF)



DESIGNED AND MANUFACTURED BY WESTQUIP DIESEL SALES

EDMONTON 780.960.5560 CALGARY 403.261.0601 VANCOUVER 778.705.0743





ELECTRICAL SPECIFICATIONS:

Voltage	Frequency	P.F.	Amps (Prime/Standby)	Prime Output (kW/kVA)	Standby Output (kW/kVA)
120/240 - 1PH	60Hz	1.0	417/458	100/100	110/110
120/208 - 3PH	60Hz	0.8	347/383	100/125	110/138
277/480 - 3PH	60Hz	0.8	150/166	100/125	110/138
347/600 - 3PH	60Hz	0.8	120/133	100/125	110/138

ENGINE SPECIFICATIONS:

- Isuzu Model: 4HK1X Liquid Cooled Diesel
- 174HP/129kW @ 1800 RPM
- 12V electrics
- Electric and self priming fuel lift pump
- Wastegate Turbo and Charge Air Cooler
- SCR, DOC and EGR
- Fan type- Pusher
- 500 hour oil change interval
- Single side service for filters
- **GENERATOR SPECIFICATIONS:**
- · Stamford Generator; UCI Series
- Single Bearing, Brushless
- Automatic Voltage Regulator (AVR Controlled)
- +/- 1% Voltage Regulation
- Winding- single or three phase

- EPA Tier 4 Final
- In-line 4 cylinder, 4 Stroke
- Displacement: 5.2L
- · Glow plugs cold starting aid
- +/- 0.25% Electronic engine control
- High pressure common rail and direct injection
- Fan, belt, and radiator core guards
- Crankcase vent heater kit to prevent freeze-up
- Crankcase pressure safety switch
- IP23 Enclosure Protection
- Class H Insulation
- 1 Year Warranty
- UL/CSA Approved





DESIGNED AND MANUFACTURED BY WESTQUIP DIESEL SALES

EDMONTON 780.960.5560 CALGARY 403.261.0601 VANCOUVER 778.705.0743





GENERATOR CONTROL PANEL

Key Features:

- Digital genset controller
- Full LCD display

Full display of:

- Oil Pressure
- Engine Temperature
- Fuel and DEF Level
- AC Voltage
- Diagnostic Trouble Codes

Safety Shutdowns and Warnings:

- Low Oil Pressure
- Under/Over AC Voltage
- Under/Over Battery Voltage
- Low DEF Level (Warning)

Optional Features:

• Remote Telematics Monitoring System

- Manual and Auto Start/Stop function
- · User friendly front panel buttons
- Engine Hours
- RPM
- Battery Voltage
- Hz Frequency
- High Coolant Temperature
- Engine Under/Over Speed (Hz/RPM)
- Low Fuel Level (Warning)
- 3-Phase AC Current (Amperage) Display





DESIGNED AND MANUFACTURED BY WESTQUIP DIESEL SALES

EDMONTON 780.960.5560 CALGARY 403.261.0601 VANCOUVER 778.705.0743





FUEL & DEF SYSTEM:

- · Diesel Fuel with SCR / DEF System
- DEF Tank Capacity: 28L
- Lockable DEF fill cap
- DEF Level Gauge is displayed on control panel
- · Heated DEF tank and piping
- Optional Sub-Base Fuel Tank Available (400L)

FUEL CONSUMPTION:

- 100% Load—26.9L/hr / 7.1 (US) gph
- 75% Load— 20.7L/hr / 5.5 (US) gph
- 50% Load— 14.7L/hr / 3.9 (US) gph

DEF CONSUMPTION:

- Approximately 3% of fuel consumption
- Minimum DEF Runtime: 35hr @ 100% Load

DIMESIONS OPEN SKID: (APPROX)

Standard Package Dimensions (max dimensions)

• Length: 81" / 2057mm (95"/ 2413mm with Automatic Load Bank)

Width: 52" / 1325mmHeight: 65" / 1659mm

• Weight: 3950lb / 1780kg (ready to run with battery and full DEF tank)

SOUND LEVEL

Open Skid Model

• No Load, @ 7m (23ft) - 82dB(A)

• Full Load, @ 7m (23ft) - 84dB(A)

WARRANTY: all models are covered by a comprehensive limited warranty

• Package: 1 Year / Unlimited Hours

• Isuzu Engine: Major components - 5 year/5000hr; All other components - 1 year unlimited hours

• Stamford Generator: 1 Year / Unlimited hours







OPTIONAL ACCESSORIES:

ENGINE SYSTEM

- Engine coolant heater—120V
- Battery charger—120V
- Battery blanket—120V
- · Battery disconnect lockout switch
- · Thermostatic radiator shutter kit
- Diesel-fired engine coolant heater (hydronic)
- Positive Air Safety Shutoff Valve
- Sub-base fuel tank 400L/90gal



- Main Circuit Breaker (120/240V 1PH; 120/208V 3PH; 277/480V 3PH; 347/600V 3PH)
- Electrical Distribution Panel- customized build; full load center; Square D components
- AC Amperage metering package. Display 3-Phase AC Amperage (standard feature on this model)

LOAD BANK MANAGEMENT SYSTEM

- 30kW Automatic load bank control system will improve performance and reliability of Tier 4 engines during critical operations.
- Load bank will automatically operate during 'light load' conditions preventing wet stacking and soot build-up in the exhaust system.
- Integrally mounted load bank for aesthetics and optimal performance.









DESIGNED AND MANUFACTURED BY WESTQUIP DIESEL SALES

EDMONTON 780.960.5560 CALGARY 403.261.0601 VANCOUVER 778.705.0743

