



WQ50T4 Open Skid Model



WQ50T4-ENCL Enclosed Model

Available in Open Skid and Enclosed Models

STANDARD FEATURES:

- JCB Liquid Cooled Engine (NO Urea/DEF; NO Shutdowns for regen; No Exhaust After-Treatment)
- Stamford Generator with Automatic Voltage Regulator—CSA approved
- Heavy duty steel skid base with anti-vibration isolation
- · Digital generator controller with user friendly display and auto start/stop functionality
- Electronic governing- excellent frequency and load pick-up
- · Central lifting point
- Safety shutdown protection (low oil pressure/high coolant temp/over & under speed/crankcase pressure)
- Operator Manuals
- Serviced and 100% Load Tested

Voltage	Frequency	P.F.	Amps	Prime Output (kW/kVA)	Standby Output (kW/kVA)
120/240 - 1PH	50/60Hz	1.0	187	45/45	48/48
120/208 - 3PH	50/60Hz	0.8	155	45/56	48/60
277/480 - 3PH	50/60Hz	0.8	67	45/56	48/60
347/600 - 3PH	50/60Hz	0.8	54	45/56	48/60









ENGINE SPECIFICATIONS:

- JCB 4.4L Stage IIIB / Tier 4 Final Liquid Cooled Diesel
- 74Hp @ 1800 RPM; 74HP @ 1500 RPM
- 12V electrics
- Electric and self priming fuel lift pump
- Variable Geometry Turbocharger
- Exhaust Gas Recirculation
- 500 hour oil change interval

GENERATOR SPECIFICATIONS:

- Stamford Generator
- Single Bearing, Brushless
- Automatic Voltage Regulator (AVR Controlled)
- +/- 1% Voltage Regulation

GENERATOR CONTROL PANEL FEATURES:

• DISPLAYS:

Engine Hours, Oil Pressure, Coolant Temperature Battery Voltage, AC Voltage, Hz Frequency,

Fuel Level, Engine RPM

- PROTECTION SAFETY SHUTDOWN & WARNINGS:
 - ⇒ Low Oil Pressure & Low Oil Level
 - ⇒ Under/Over AC Voltage
 - ⇒ Under/Over Battery Voltage
- Auto Start / Stop with AUX contacts
- Programmable Exerciser

- In-line 4 cylinder, 4 Stroke
- Displacement: 4.4L
- · Glow plug cold starting aid
- +/- 0.25% Electronic engine control
- No Exhaust After Treatment No DOC or DPF
- Fan, belt, and core guards
- High pressure common rail and direct injection
- IP23 Enclosure Protection
- Class H Insulation
- 1 Year Warranty
- UL/CSA Approved



- ⇒ High Coolant Temperature
- ⇒ Under/Over Engine Speed
- ⇒ Low Fuel Level
- AC Current (Amp) Metering Display (optional)
- Remote telematics monitoring system (optional)

DIMESIONS OPEN SKID: (APPROX)

Standard Package Dimensions including lift bail assembly and battery tray (max dimensions)

- Length: 83.25" / 2114mm (77" / 1956mm without battery)
- Width: 30.5" / 774mm
- Height: 55" / 1397mm (top of muffler)
- Weight: 2500lb / 1134kg (2345lb / 1064kg without battery)





DESIGNED AND MANUFACTURED BY WESTQUIP DIESEL SALES







WQ50-ENCL was designed with single side service. Hinged left hand side door accesses filters.

A removable access panel on right hand side allows service and space savings when installing the generator where space is restricted.



ENCLOSURE SPECIFICATIONS:

- Powder coated weather-proof enclosure
- Rain proof air intake ducts
- Stainless steel door handles and hinges
- · Gasket lined doors

FUEL SYSTEM:

- · Single wall steel fuel tank
- Capacity: 312L / 68 IMP Gal
- Vented fill cap
- Fuel Level Gauge (displayed on panel)

- Lockable doors
- Rust-proof fasteners with nylon washer
- Optional air discharge hood (plenum)
- Optional custom color

FUEL CONSUMPTION:

- 100% Load—12.4L/hr
- 75% Load—9.8L/hr
- 50% Load—7.2L/hr
- 25% Load—3.8L/hr

ENCLOSED GENERATOR SET DIMENSION AND WEIGHT:

Generator (Skid Unit)

- Dimensions (LxWxH) 89" x 36.5" x 69"H (2260mm x 953mm x 1752mm) Height: top of muffler
- Dry Weight: 3350lb (1519kg) Wet Weight: 3894lb (1766kg)

Mobile Generator (includes standard Tandem Axle Trailer Package)

- Dimensions (LxWxH): 137" x 69" x 89" (3480mm x 1752mm x 2260mm)
- Dry Weight: 4600lb (2086kg) Wet Weight: 5144lb (2333kg)

SOUND LEVEL

Standard Enclosure

- No Load, @ 7m (23ft) 78 dB(A)
- Full Load, @ 7m (23ft) 79 dB(A)

Enclosure with Air Discharge Plenum (*optional***)**

- No Load, @ 7m (23ft) 74 dB(A)
- Full Load, @ 7m (23ft) 75 dB(A)



DESIGNED AND MANUFACTURED BY WESTQUIP DIESEL SALES





OPTIONAL ACCESSORIES:

ENGINE SYSTEM

- Engine coolant heater—120V
- Battery charger—120V
- Battery blanket—120V
- Battery disconnect lockout switch
- Thermostatic radiator shutter kit
- Diesel-fired engine coolant heater (hydronic)
- Positive Air Safety Shutoff Valve
- Sub-base fuel tank 385L/85gal (71.5" x 30.5" x 14")



AC ELECTRICAL SYSTEM

- Main Circuit Breaker (120/240V 1PH; 120/208V 3PH; 277/480V 3PH; 347/600V 3PH)
- Electrical Distribution Panel- customized build; full load center; Square D components
- AC Amperage metering package. Will display AC Amperage on upgraded genset control panel.



PARALLELING LOAD MANAGEMENT SYSTEM

- Available with paralleling genset control package
- Synchronize multiple genset to increase your power output
- Load Management will increase fuel efficiency and create redundancy
- Parallel generators will automatically turn on and off to manage load requirements.





DESIGNED AND MANUFACTURED BY WESTQUIP DIESEL SALES





OPTIONAL ACCESSORIES:

ENCLOSURE

- Winter front- Radiator cold weather winter cover. Fits standard enclosure model.
- Air Discharge Plenum- Reduce DB(A) noise level with addition of an air discharge plenum. Reduction of up to 8-10dBA at air discharge (measured at 1m).



TRAILER

- Tandem axle Transport Canada/DOT approved trailer
- 15" ST205/75R15 Tires
- 3500lb torsion axles
- Front leveling jack
- 3" Pintle eye coupler or 2-5/16" ball coupler
- Safety chains











WARRANTY: all models are covered by a comprehensive limited warranty

- Package: 1 Year / Unlimited Hours
- JCB Engine: Major components 2 year unlimited hours, All other components 1 year unlimited hours
- Stamford Generator: 1 Year / Unlimited hours



